

E CirCarLife

Intelligent recharging solutions for electric vehicles

TRIO Quick Charger

Circontrol Trio Quick Charger CCL-QPC (compact combined quick charged) combine CHAde-MO (DC 50kW), Combo 2 (DC 50kW) and AC 43kW.

Designed to support dual protocol CHAdeMO and CCS (combo 2) to cover all users needs, making suitable for business and commercial fleets as well as petrol station along the roads.

The compact combined version has been adapted with latest communication protocols OCPP and XML. Circontrol offers an innovative SCADA software for remote control and as a management tool.

Charging operator can friendly access to status information, graphics and charge reports according historical data registered.

Technical Features User interface
Quick Charging in 15 minutes
8" LCD screen for user interaction
Start, Stop and emergency buttons
Light indications for status
RFID identification and prepayment
Charging management
Mode 3 and mode 4 locking mechanism
Real time energy metering
Time and consumption based prepayment modes
Simultaneous AC & DC charging with maximum demand control
Communications and protoco
Remote control and monitoring of the unit through standard XML & HTML
OCPP protocol integration
Ethernet 10/100BaseTX communication and 3G (Optional)
Security & Protection
IP Rate: IP54
Temperature range -30°C to +45°C
Protection against overloads, short-circuits and insulation faults with an automatic switch

EV standards: IEC 62196-3, IEC 61851-1, CHAdeMO and CCS (combo 2)

