

Commercial Electric Vehicle Charging Stations

FEATURES

PRODUCT FEATURES

Modern compact design with robust construction for maximum durability

- Rapid Level 2 charging—7.2 - 7.7kW output provides up to 8x faster charging versus standard Level 1
- Suitable for indoor and outdoor use, NEMA 4 rated
- Multiple charge cable length selections to fit your charging area location needs
- Single or dual charging station (port) options
- EvoReel® with standard 3-foot interconnect and 22-foot charge cable, and the optional, industry's longest, 30 foot charge cable, can be mounted on wall, pedestal or overhead.

OPTIONAL ACCESSORIES

Cable management solutions for the ultimate cord convenience, cleanliness and safety

- EvoReel with Charge Cable—self retracting and locking for overhead, wall or pedestal mount
- Retractor—spring loaded tether, suspends cable to effortlessly draw cable back for convenient storage Holster

Flexible open network OCPP (wi-fi & LTE cellular) and non-networked charging stations



EvoReel® with Charger Cable

Charging Station

Holster



Commercial Electric Vehicle Charging Stations

CABLE MANAGEMENT OPTIONAL ACCESSORIES

Select the appropriate charging station for your installation needs. Consider optional accessories for additional cable management solutions.

EVOCHARGE® EVSE 30A, 7.2KW EVOREEL® AND HOLSTER

Part Number	Cable Length	Power Connection	Ports	Mounting
EVC4AA0C2B1A1	22 ft.	Plug-In*	Single	Wall
EVC4AA0D2B1A1	30 ft.	Plug-In*	Single	Wall
EVC4AA0C1B1B3	22 ft.	Hardwire	Dual	6 ft. Pedestal
EVC4AA0D1B1B3	30 ft.	Hardwire	Dual	6 ft. Pedestal

EVOCHARGE IEVSE® 30A, 7.2KW, WI-FI AND OCPP DEMAND RESPONSE AND LOCAL LOAD MANAGEMENT COMPATIBLE WITH EVOREEL AND HOLSTER**

Part Number	Cable Length	Power Connection	Ports	Mounting
EVC4AB0C2B1A1	22 ft.	Plug-In*	Single	Wall
EVC4AB0D2B1A1	30 ft.	Plug-In*	Single	Wall
EVC4AB0C1B1B3	22 ft.	Hardwire	Dual	6 ft. Pedestal
EVC4AB0D1B1B3	30 ft.	Hardwire	Dual	6 ft. Pedestal

EVOCHARGE IEVSE® PLUS 30A, 7.2KW, WI-FI OR 4G-LTE CELLULAR, RFID CARD READER AND OCPP, DEMAND RESPONSE AND LOCAL LOAD MANAGEMENT COMPATIBLE WITH EVOREEL AND HOLSTER**

Part Number	Cable Length	Power Connection	Ports	Mounting
EVC4AC0C1B1A1	22 ft.	Hardwire	Single	Wall
EVC4AC0D1B1A1	30 ft.	Hardwire	Single	Wall
EVC4AC0C1B1B3	22 ft.	Hardwire	Dual	6 ft. Pedestal
EVC4AC0D1B1B3	30 ft.	Hardwire	Dual	6 ft. Pedestal

* For hardwired input circuit connection, input plug can simply be removed by a certified electrician during installation.
 ** Optional OCPP requires the use of a third-party network service provider. Charges will apply. Please visit our website

OPTIONAL ACCESSORIES (Contact us for Part Number)

Part	Interconnect Length	Cable Lengths (excluding the retractor)
EvoReel	3 ft.	22 ft. and 30 ft.
EvoReel	20 ft.	22 ft. and 30 ft.
Cable Retractor EVC0201	N/A	N/A

Part Number	Pedestal Height
Pedestal EVC0402	4 ft.
Pedestal EVC0404	6 ft.
Pedestal EVC0404	8 ft.

INPUT CIRCUIT INFORMATION

Level 2 EVSE Charging Stations are SAE J1772, 208-240VAC, Single Phase and require a dedicated 40A supply circuit.*

* All EvoCharge EVSE products can be field adjusted for use with 30A or 20A supply circuit.



EvoReel with Cable



Charging Station

Optional Accessories Shown



Cable Retractor



Dual Port 6 ft. Pedestal with EvoReel® shown

Single Port 4 ft. Pedestal shown